

1. IDENTIFICATION

Product identifier
Product Name EVERCOAT FIBERGLASS-AUTO RESIN

Other means of identification
Product Code 100498_100499_100500

Recommended use of the chemical and restrictions on use
Recommended Use Resin. For professional use only.
Uses advised against Uses other than recommended use.

Details of the supplier of the safety data sheet
Manufacturer Address

 ITW Evercoat
 6600 Cornell Road
 Cincinnati, Ohio 45242
 Telephone: 513-489-7600

24-hour emergency phone number

 CHEMTREC: 1-800-424-9300
 INTERNATIONAL: 1-703-527-3887

May Also Be Distributed by:

 ITW Permatex Canada
 101-2360 Bristol Circle
 Oakville, ON Canada L6H 6M5
 Telephone: (800) 924-6994

E-mail address: Info@evercoat.com

2. HAZARDS IDENTIFICATION

Classification
OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

Label elements
Emergency Overview
Signal word
Danger

 Harmful if swallowed or if inhaled
 Causes skin irritation
 Causes serious eye irritation
 May cause cancer
 Suspected of damaging fertility or the unborn child
 Causes damage to organs through prolonged or repeated exposure
 Flammable liquid and vapor



Appearance Pink

Physical state Liquid

Odor Pungent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Use only outdoors or in a well-ventilated area
Wear eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth
In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin. Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Styrene	100-42-5	15-35

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Use dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Flammable. Vapors may travel to source of ignition and flash back. Vapors may form explosive mixtures with air.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear fire/flame resistant/retardant clothing. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). See section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use personal protective equipment as required.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not breathe dust/fume/gas/mist/vapors/spray. When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in confined areas. Never pierce, drill, grind, cut, saw or weld any empty container.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from sunlight, ignition sources and other sources of heat. Keep tightly closed in a dry and cool place. Keep cool. Protect from sunlight. Store in a well-ventilated place. Keep cool. Store at temperatures not exceeding 25 °C / 77 °F.

Incompatible materials Acids, Bases

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Styrene 100-42-5	STEL: 20 ppm TWA: 10 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m ³ (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m ³ Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Ventilation systems Use exhaust ventilation to keep airborne concentrations below exposure limits

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses or goggles if splashing is likely to occur. Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Pink
Odor	Pungent
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	146 °C / 294.8 °F	
Flash point	32 °C / 89.6 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	No information available	
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	490 °C / 914 °F	
Hyphen	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC content	<35%
Applied	VOC (as applied*- 2% by wt hardener- less exempts and water):0.38 lbs/gal or 45.53 g/L
Packaged	3.3 lbs/gal
Density	9.4 lbs/gal
Bulk density	No information available
SADT (self-accelerating decomposition temperature)	No information available

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Acids, Bases

Hazardous Decomposition Products

Thermal decomposition can lead to release of toxic/corrosive gases and vapors

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 11.7 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5	A3	Group 2A	Reasonably Anticipated	X

IARC (International Agency for Research on Cancer)
Group 2A - Probably Carcinogenic to Humans
Not classifiable as a human carcinogen
 NTP (National Toxicology Program)
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Chronic toxicity May cause adverse liver effects. Contains a known or suspected reproductive toxin.
Target organ effects Central nervous system, Eyes, Liver, Reproductive system, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	1031 mg/kg
ATEmix (dermal)	2088 mg/kg
ATEmix (inhalation-dust/mist)	1.6 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical name	Partition coefficient
Styrene 100-42-5	2.95

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN/ID No	UN3269
Proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing Group	III

IATA

UN number or ID number	UN3269
Proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing group	III

IMDG

UN number or ID number	UN3269
Proper shipping name	Polyester Resin Kit
Transport hazard class(es)	3
Packing Group	III

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not determined
ENCS	Not determined
IECSC	Complies
KECL	Not determined
PICCS	Not determined
AICS	Complies

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Styrene 100-42-5	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Styrene 100-42-5	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 1	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
 HMIS (Hazardous Material Information System)

Revision Date 26-Apr-2021

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet