

Page 1/13 Printing date: 17.03.2023 Revision date: 17.03.2023 Version no. 17

SAFETY DATA SHEET According to 1907/2006/EC, Article 31

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: BODY 699 CLEAR HS SR 2:1

· Article number: 465

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: HB BODY S.A. B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022, SINDOS THESSALONIKI,GREECE Ph: +30 2310 790 000 Fax: +30 2310 790 033 www.hbbody.com email: hbbody@hbbody.com

Further information obtainable from: HB BODY S.A.
B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022, SINDOS
THESSALONIKI,GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI Pharmacy Department, Royal Hospital Suite Grosvenor Road Belfast Telephone: +44 28 90 63 2032 Fax: +44 28 90 24 80 30 Emergency telephone: 844 892 0111 E-mail address: nirdic.nirdic@belfasttrust.hscni.net

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



H226 Flammable liquid and vapour.





H361d Suspected of damaging the unborn child.



Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

[•] 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling: toluene
- Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H361d Suspected of damaging the unborn child.
- H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210
- P240 Ground and bond container and receiving equipment.
- Use explosion-proof [electrical/ventilating/lighting] equipment. P241

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction. Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

[•] 2.3 Other hazards

- [·] Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Page 3/13 Printing date: 17.03.2023 Revision date: 17.03.2023 Version no. 17

Trade name: BODY 699 CLEAR HS SR 2:1

[.] Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 01-2119488216-32-001 01-2119488216-32-002 01-2119488216-32-003	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	40-<45%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-0007 01-2119475791-29	2-methoxy-1-methylethyl acetate	5-<10%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 RTECS: XS 5250000 Reg.nr.: 01-2119471310-51-0003 01-2119471310-51-0003 01-2119471310-51-0002 01-2119471310-51-0002	3 5 2	≥3-<5%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-0007	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	1-<5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000 Reg.nr.: 01-2119485493-29-007 01-2119485493-29-003 01-2119485493-29-005 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	1-<5%
CAS: 41556-26-7 EINECS: 255-437-1	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	≥0.25-<0.9%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

[•] After inhalation: In case of unconsciousness place patient stably in side position for transportation.

[·] After skin contact:

Immediately wash with water and soap and rinse thoroughly.

In case of skin contact DO NOT clean effected area with solvents or thinners. Take off all contaminated clothing at once. Wash skin thoroughly with neutral pH soap and water. In any suspicion that skin irritation persists call a doctor.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: If symptoms persist consult doctor.

Continue on page 4 GB

*

Trade name: BODY 699 CLEAR HS SR 2:1

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Open and handle receptacle with care.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

[·] Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

[•] 8.1 Control parameters

[•] Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

· Regulatory information WEL: EH40/2020

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

[·] Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- \cdot Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the base of the different substances in the preparation.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- · Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information	
· Appearance:	
Form: Colour:	
· Odour:	Colourless Characteristic
· Odour threshold:	Not determined.
· pH-value:	Mixture is non-soluble (in water).
[.] Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137-143 °C (1330-20-7 xylene)
[.] Flash point:	23 - 60 °C
[.] Flammability (solid, gas):	Flammable.
[.] Autoignition temperature:	315 °C
[.] Decomposition temperature:	Not determined.
[.] Ignition temperature:	Product is not selfigniting.
[.] Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
[·] Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
[.] Vapour pressure at 20 °C:	6.7 hPa
[·] Density at 20 °C:	0.95445 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.

· Evaporation rate	Not determined.
 Solubility in / Miscibility with water: 	Fully miscible.
· Partition coefficient: n-octanol/wate	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
⁻ Solvent content:	
Organic solvents:	53.5 %
VOC (EC)	510.2 g/l
Solids content (volume):	1.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- . **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability
- [•] Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- * 10.3 Possibility of hazardous reactions No dangerous reactions known.
- . 10.4 Conditions to avoid No further relevant information available.
- * **10.5 Incompatible materials:** No further relevant information available.
- * **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 4,860 mg/kg (rabbit) Inhalative LC50/4 h 26.7 mg/l

1330-20-7 xylene

OralLD504,300 mg/kg (rat)DermalLD502,000 mg/kg (rabbit)InhalativeLC50/4 h 11 mg/l (ATE)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat) Dermal LD50 12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- [•] **12.3 Bioaccumulative potential** No further relevant information available.
- * **12.4 Mobility in soil** No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- [·] Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

- * PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

* **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

[.] Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Page 9/13 Printing date: 17.03.2023 Revision date: 17.03.2023 Version no. 17

*

Trade name: BODY 699 CLEAR HS SR 2:1

- [·] Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information		
ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name	011203	
ADR	UN1263 PAINT	
· IMDG, IATA	PAINT	
14.3 Transport hazard class(es)		
ADR		
Class	3 (F1) Flammable liquids.	
·Label	3	
· IMDG, IATA		
Class	3 Flammable liquids.	
	3	
14.4 Packing group		
[·] ADR, IMDG, IATA [·] 14.5 Environmental hazards:	III	
[•] Marine pollutant:	No	
14.6 Special precautions for user	Warning: Flammable liquids.	
· Hazard identification number (Kemler code):	30	
· EMS Number:	F-E, <u>S-E</u>	
· Stowage Category	А	
14.7 Transport in bulk according to Annex II of		
Marpol and the IBC Code	Not applicable.	
[.] Transport/Additional information:		
ADR		
· Limited quantities (LQ)	5L	
 Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
[·] Tunnel restriction code	D/E	
	Continue on p	

Continue on page 10 GB

- · IMDG
- Limited quantities (LQ)
- Excepted quantities (EQ)

5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 1263 PAINT, 3, III

· UN "Model Regulation":

SECTION 15: Regulatory information •3Y

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



- Signal word Warning
- · Hazard-determining components of labelling: toluene
- Hazard statements
- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H361d Suspected of damaging the unborn child.
- H412 Harmful to aquatic life with long lasting effects.
- · Precautionary statements
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P405 Store locked up. P501
 - Dispose of contents/container in accordance with local/regional/national/international regulations.
- [·] Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.

Continue on page 11 GR

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- · Contact:
- HB BODY S.A Ms Olympia Stamkou Ph: +30 2310 790 032 fax: +30 2310 790 033
- email: stamkou@hbbody.com
- * Data compared to the previous version altered.

GB Continue on page 12

Annex: Exposure scenario

Short title of the exposure scenario

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

• Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture

[•] Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- Conditions of use According to directions for use.
- · Duration and frequency Frequency of use:

[•] Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- [·] Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- [·] Used amount per time or activity Smaller than 100 g per application.

[•] Other operational conditions

[•] Other operational conditions affecting environmental exposure

- No special measures required.
- Use only on hard ground.

• Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid long-term or repeated skin contact.

Avoid contact with eyes.

- [·] Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

[•] Risk management measures

[·] Worker protection

· Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

Provide explosion-proof electrical equipment.

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Not required.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Pregnant women should strictly avoid inhalation or skin contact.

Continue on page 13 GB

Avoid contact with the eyes. Tightly sealed goggles

- · Measures for consumer protection
- Ensure adequate labelling.

Observe consumer information and advice on safe use.

- [•] Environmental protection measures
- · Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- Do not allow to reach sewage system.
- · Soil

The product is only processed over the concrete collecting basin.

- Prevent contamination of soil.
- **Disposal measures** Ensure that waste is collected and contained.
- [.] Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- [.] Consumer

This product is to be used by professional technitians only.

Not relevant for this Exposure Scenario.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.