Page: 1 of 8

	PRODUCT AND COMPANY I	DENTIFICATION
Product Name: Company Name:	Aircraft Aerosol Non MeCl W. M. Barr 2105 Channel Avenue	Phone Number: (901)775-0100
	Memphis, TN 38113	
Web site address:	www.wmbarr.com	
Emergency Contact:	3E 24 Hour Emergency Contact	(800)451-8346
Information:	W.M. Barr Customer Service	(800)398-3892
ntended Use:	Paint/Varnish Remover	
Product Code:	EAR2000	
	2. HAZARDS IDENTIFI	CATION
Flammable Aerosols, Categ Gas Under Pressure, Comp Simple Asphyxiant Skin Corrosion/Irritation, Ca Serious Eye Damage/Eye Irr Germ Cell Mutagenicity, Cat	ressed gas ategory 1B ritation, Category 1 tegory 1B	
Carcinogenicity, Category 1		
Specific Target Organ Toxic	city (single exposure), Category 3	
GHS Signal Word: GHS Hazard Phrases:	Danger Extremely flammable aerosol.	
	Containers gas under pressure; may ex Causes severe skin burns and eye dam Causes serious eye damage. May cause drowsiness or dizziness. May cause genetic defects.	
	Containers gas under pressure; may ex Causes severe skin burns and eye dam Causes serious eye damage. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. May displace oxygen and cause rapid s	nage.
	Containers gas under pressure; may ex Causes severe skin burns and eye dam Causes serious eye damage. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer.	hage. Suffocation. Is have been read and understood. es/hot surfaces No smoking. other ignition source. burn, even after use.

Page: 2 of 8

SAFETY DATA SHEET Aircraft Aerosol Non MeCl

	Specific treatment see label. Wash contaminated clothing before reuse.
GHS Storage and Disposal	Store container tightly closed in well-ventilated place.
Phrases:	Store locked up.
	Protect from sunlight and store in well-ventilated place.
	Do not expose to temperatures exceeding 50 °C/122 °F.
	Dispose of contents/container according to local, state and federal regulations.
Potential Health Effects (Acute and Chronic):	Referenced above.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
109-99-9	Tetrahydrofuran {THF; Diethylene oxide; 1,4-Epoxybutane}	15.0 -40.0 %
67-64-1	Acetone {2-Propanone}	30.0 -60.0 %
68476-86-8	Liquified petroleum gas, sweetened {propane, isobutane, n-butane}	7.0 -13.0 %
7664-41-7	Ammonia {Anhydrous Ammonia; R-717}	0.5 -1.5 %
929-06-6	2-(2-Aminoethoxy) ethanol	0.1 -1.0 %

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

Information

4. FIRST AID MEASURES

Emergency and First Aid Procedures:	Skin: Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.				
	Eyes: Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.				
	Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.				
	Ingestion: If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.				
Signs and Symptoms Of Exposure:	See Potential Health Effects.				
Note to Physician:					

Revision: 12/09/2019 Supersedes Revision: 03/06/2019

	5. FIRE FIGHTING MEASURES			
Flammability Classification:	Level 3			
Flash Pt:	0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)			
Explosive Limits:	LEL: N.D. UEL: N.D.			
Autoignition Pt:	N.D.			
Suitable Extinguishing Media	:Use carbon dioxide, dry powder, or alcohol resistant foam.			
Unsuitable Extinguishing Media:	Do not use straight streams of water. If water is used, use a water spray or fog.			
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.			
Flammable Properties and Hazards:	Danger! Flammable. Keep away from heat, sparks, flame, and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Beware of static electricity that may be generated by synthetic clothing and other sources.			
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide, hydrogen chloride, chlorine, phosgene			
	6. ACCIDENTAL RELEASE MEASURES			
Steps To Be Taken In Case Material Is Released Or Spilled:	Vapors may cause flash fire or ignite explosively. Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc. Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. Large spills: Dike far ahead of spill for later disposal. Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.			
	7. HANDLING AND STORAGE			
Precautions To Be Taken in Handling:	Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.			
	Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.			
	Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.			
Licensed to W.M. Barr and Company	GHS format			

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing:

Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Do not store near flames or at elevated temperatures.

Keep container tightly closed when not in use - Tetrahydrofuran may form peroxides when exposed to air.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
109-99-9 Tetrahydrofuran {TH Diethylene oxide; 1,4-Epoxybuta		TLV: 50 ppm STEL: 100 ppm	
	OSHA PELs	PEL: 200 ppm	
67-64-1 Acetone {2-Propanon	e} ACGIH TLV	TLV: 500 ppm STEL: 750 ppm	
	OSHA PELs	PEL: 1000 ppm	
7664-41-7 Ammonia {Anhydro Ammonia; R-717}	us ACGIH TLV	TLV: 25 ppm STEL: 35 ppm	
	OSHA PELs	PEL: 50 ppm	
Respiratory Equipment (Specify Type):	properly fitted NIOSH a supply respirator or loo For OSHA controlled w	nadequate ventilation or fresh air, wear a p approved self-contained breathing apparate use fitting hood. work places and other regular users - Use c eered air control systems designed to prev	us or powered air
	A dust mask does not p	provide protection against vapors.	
Eye Protection:	contact, irritation, or inj splashing or spraying o	ace shields are recommended to safeguard ury. Chemical goggles or face shields are of chemical is possible. A faceshield provid contact to the face and eyes.	recommended when
Protective Gloves:	film gloves offer the be	uch resistance to the chemical ingredients st protection. Consult your glove supplier f ntaminated with product should be discard	or additional
Other Protective Clothing:	such as impermeable a clean any clothing or p	thods can dictate use of additional protecti aprons, etc., to minimize exposure. Before rotective equipment that has been contami other protective equipment that cannot be	e reuse, thoroughly inated by prior use.
Engineering Controls (Ventilation etc.):	•	es, local exhaust ventilation, or other engine below recommended exposure limits.	eering controls to
	well ventilated, DO NO	e ventilation to prevent buildup of vapors. In T use this product. Do not use in areas wi ntrate, such as basements, bathrooms or s	here vapors can
	Whenever possible, us	e outdoors in an open air area. If using ind	doors open all windows
Licensed to W.M. Barr and Company			GHS format

Revision: 12/09/2019 upersedes Revision: 03/06/2019

	Supersedes Revision: 03/06/2019
	and doors and maintain a cross ventilation of moving fresh air across the work area. If
	strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering STOP ventilation is inadequate. Leave area immediately and move to
	fresh air.
Work/Hygienic/Maintenance Practices:	Wash hands thoroughly after use and before eating, drinking, or smoking.
	Do not eat, drink, or smoke in the work area.
	Facilities storing or handling this material should be equipped with an emergency
	eyewash and safety shower.
	PHYSICAL AND CHEMICAL PROPERTIES
Physical States:	[X]Gas [X]Liquid []Solid
Appearance and Odor:	Off-white opaque viscous liquid
	Aromatic with ammona odor Odor threshold not determined
pH:	N.D.
Melting Point:	N.D.
Boiling Point:	N.D.
Flash Pt:	0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Evaporation Rate:	N.D.
Flammability (solid, gas):	EXTREMELY FLAMMABLE.
Explosive Limits:	LEL: N.D. UEL: N.D.
Vapor Pressure (vs. Air or	N.D.
mm Hg):	N.D.
Vapor Density (vs. Air = 1):	N.D.
Specific Gravity (Water = 1):	.8534
Density:	7.101 LB/GL
Solubility in Water:	N.D.
Octanol/Water Partition Coefficient:	N.D.
Percent Volatile:	95.68 % by weight.
VOC / Volume:	49.6000 % WT
Autoignition Pt:	N.D.
Decomposition Temperature:	N.D.
Viscosity:	N.D.
Additional Physical	Flash Point is for liquid contents.
Information	
	10. STABILITY AND REACTIVITY
Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	**None known.
Incompatibility - Materials To Avoid:	Bases, oxygen, sodium, potassium, strong oxidizers, reactive metals, strong acids
Hazardous Decomposition or Byproducts:	Carbon monoxide, carbon dioxide
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Licensed to W.M. Barr and Company	GHS format

Page: 6 of 8

Conditions T Hazardous R		**None known.						
		11. TOXICOLOGICAL IN	FORMA					
Toxicological Information:		This product has not been tested as a whole. Refer to section 2 for acute and chronic effects. CAS# 109-99-9: Other Studies:, TDLo, Oral, Rat, 26280. mg/kg. Result: Liver: Tumors. Kidney, Ureter, Bladder: Kidney tumors. - Toxicologist., Soc. of Toxicology, Inc., 475 Wolf Ledge Parkway, Akron, OH 44311, Vol/p/yr: 60,286, 2001						
Chronic Toxi	cological	CAS# 67-64-1: Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe. Result: Behavioral: Change in motor activity (specific assay). Behavioral: Alteration of classical conditioning. - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946						
Effects:	cological		This product has not been tested as a whole.					
Carcinogenio	city/Other	ACGIH A4 - Not Classifiable as a Hur	nan Carcir	nogen.				
CAS#	Hazardous C	omponents (Chemical Name)	NTP	IARC	ACGIH	OSHA		
109-99-9	Tetrahydrofura 1,4-Epoxybuta	an {THF; Diethylene oxide; ane}	n.a.	n.a.	n.a.	n.a.		
67-64-1	Acetone {2-P	ropanone}	n.a.	n.a.	A4	n.a.		
68476-86-8	Liquified petro n-butane}	leum gas, sweetened {propane, isobutane,	n.a.	n.a.	n.a.	n.a.		
7664-41-7	Ammonia (An	hydrous Ammonia; R-717}	n.a.	n.a.	n.a.	n.a.		
929-06-6	2-(2-Aminoeth	oxy) ethanol	n.a.	n.a.	n.a.	n.a.		
		12. ECOLOGICAL INFO	DRMAT	ION				
General Ecol	ogical	This product has not been tested as a	whole.					
		13. DISPOSAL CONSID	ERATI	ONS				
Naste Dispo	sal Method:	Dispose in accordance with all application	able local,	state, and fe	deral regulati	ons.		
		14. TRANSPORT INFC	RMAT	ION				

Revision: 12/09/2019 Supersedes Revision: 03/06/2019

DOT Prop DOT Haza UN/NA Nu		ne: Aerosols, flammable, corrosive 2.1(8) FLAMMABLE, CORROSIVE UN1950			
		RINAMELE OGS	>		
LAND TRAN	SPORT (Canadian T	DG):			
•	ping Name:				
UN Numb		1950			
Hazard Cl	ass:	2.1(8) - FLAMMABLE, CORROSIVE	TDG Class	sification:	
Additional T Information:	C	he shipper / supplier may a onsumer Commodity, Limi others, as allowed under ubchapter C to ensure tha	ted Quantity, Visc 49CFR Hazmat F	cous Liquid, Does N Regulations. Please	Not Sustain Combustion
		15. REGULATOR	Y INFORMA	TION	
EPA SARA (S	uperfund Amendmen	ts and Reauthorization Act	of 1986) Lists		
CAS # 109-99-9		nents (Chemical Name) IF; Diethylene oxide;	S. 302 (EHS) No	S. 304 RQ Yes 1000 LB	S. 313 (TRI) No
67-64-1	Acetone {2-Propano	ne}	No	Yes 5000 LB	No
68476-86-8	Liquified petroleum g isobutane, n-butane}	as, sweetened {propane,	No	No	No
7664-41-7	Ammonia (Anhydrou	us Ammonia; R-717}	Yes 500 LB	Yes 100 LB	Yes
929-06-6	2-(2-Aminoethoxy) e	thanol	No	No	No
CAS #	Hazardous Compor	nents (Chemical Name)	Other US EPA o	r State Lists	
109-99-9	Tetrahydrofuran {T⊦ 1,4-Epoxybutane}	IF; Diethylene oxide;	TSCA: Inventory	v, 8A PAIR	
67-64-1	Acetone {2-Propand	ne}	TSCA: Inventory	,	
68476-86-8	Liquified petroleum g isobutane, n-butane}	as, sweetened {propane,	TSCA: Inventory	,	
7664-41-7	Ammonia (Anhydrou	us Ammonia; R-717}	CWA NPDES TSCA: Inventory	v, 8A CAIR	
929-06-6	2-(2-Aminoethoxy) e	thanol	TSCA: Inventory	v, 8A, 8A PAIR	
Additional R	equiatory Th	nis product is regulated by	the United States	s Consumer Produc	t Safety Commission
Information	ar Ad	nd is subject to certain labe ct. These requirements dif	eling requirements fer from the class	s under the Federa ification criteria and	Hazardous Substance
	re	quired for safety data shee	ets (SDS). The pr	oduct label also inc	ludes other importa

using the product.

information, including directions for use, and should always be read in its entirety prior to

LAND TRANSPORT (US DOT):

Revision: 12/09/2019 Supersedes Revision: 03/06/2019

16. OTHER INFORMATION

Revision Date:

Preparer Name:W.M. Barr EHS Dept(901)775-0100

12/09/2019

Additional Information About N.D.: Not determined.

This Product:

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.