



XXX SPECIALTY GEL ADHESIVE REMOVER

TECHNICAL DATA SHEET

 Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

XXX Specialty Gel Adhesive Remover is a solvent-based gel for removing adhesive residue as well as tar, sap, silicone, grease and oil from interior or exterior surfaces. Gel formula stays in place on vertical and horizontal panels and evaporates slower than typical solvent adhesive remover.

FEATURES

- Unique gel improves efficiency and eliminates product waste
- 50 state compliant
- Slow evaporating formula stays wet long enough to soften adhesive
- Run resistant gel stays where you spray it
- Quick acting
- Dissolves adhesive residue, tar, sap, and more
- Available in a convenient aerosol
- Ideal for use on interior or exterior surfaces

SUITABLE SUBSTRATES

- Plastic
- Leather
- Vinyl
- OEM panels
- Cured two-component finishes
- Glass
- Bare aluminum
- Bare steel

Note: Because **XXX Specialty Adhesive Remover** is a solvent-based product and can damage soluble coatings and substrates, always test **XXX Specialty Adhesive Remover** on an inconspicuous area before use. Apply only to thoroughly cured two-component paint or stable substrates.

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
77793	XXX Specialty Gel Adhesive Remover	Clear	20 oz. Aerosol

VOC Actual:

77793	5.84 #/gal (700.1 g/L)
-------	------------------------

Check local VOC regulations to ensure compliance in your area.



Check local VOC regulations to ensure compliance of all products in your area.

Always wear OSHA required (PPE) Personal Protection Equipment as outlined on the SDS and product label to ensure your safety.



HANDLING AND APPLICATION

MIXING:

Ready to use.

APPLICATION:

1. Apply **XXX Specialty Gel Adhesive Remover** directly to surface or clean cloth. Apply enough material to adequately cover the contaminants.
2. Allow the product to sit until the adhesive is dissolved and wipe away contaminants.
3. Once contaminant is removed, re-wet once more and wipe dry in one direction with a clean, lint-free cloth.
4. If **XXX Specialty Gel Adhesive Remover** dries on the surface, re-wet and wipe dry completely.

Note: Because **XXX Specialty Adhesive Remover** is a solvent-based product and can damage soluble coatings and substrates, always test **XXX Specialty Adhesive Remover** on an inconspicuous area before use. Apply only to thoroughly cured two-component paint or stable substrates.



STORAGE:

XXX Specialty Gel Adhesive Remover should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **77793** is 3 years when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:
77721	XXX Adhesion Promoter	Gallon
77723	XXX Adhesion Promoter	16 oz. Aerosol
77724	XXX Adhesion Promoter	Cone Quart
77763	XXX Universal Gun Cleaner	20 oz. Aerosol
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart
77783	XXX Specialty Adhesive Remover	20 oz. Aerosol
77784	XXX Specialty Adhesive Remover	Quart

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.



Check local VOC regulations to ensure compliance of all products in your area.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.