

Page 1/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

[·] Trade name: **SPRAY FILL**

- · Article number: 177
- · UFI: Q710-A0WY-600K-35WK

1.2 Relevant identified uses of the substance or mixture and uses advised against

- · Sector of Use
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- SU21 Consumer uses: Private households / general public / consumers
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
 Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Application of the substance / the mixture Thinner, Diluent Surface protection

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: HB BODY S.A. B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022, SINDOS THESSALONIKI,GREECE Ph: +30 2310 790 000 Fax: +30 2310 790 033 www.hbbody.com email: hbbody@hbbody.com
- Further information obtainable from: HB BODY S.A.
 B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA 57.022, SINDOS THESSALONIKI,GREECE
 Ph: +30 2310 790 000
 Fax: +30 2310 790 033
 www.hbbody.com
 email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI Pharmacy Department, Royal Hospital Suite Grosvenor Road Belfast Telephone: +44 28 90 63 2032 Fax: +44 28 90 24 80 30 Emergency telephone: 844 892 0111 E-mail address: nirdic.nirdic@belfasttrust.hscni.net Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111 Page 2/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

- ⁻ Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



. . .

- · Signal word Danger
- Hazard-determining components of labelling: butan-1-ol acetone
- · Hazard statements
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- · Precautionary statements
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Continue on page 3

Page 3/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

SAFETY DATA SHEET According to 1907/2006/EC, Article 31 as amended by 220/878

Trade name: SPRAY FILL

[·] Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

[·] Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

[•] Description: Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

Bangerede compenente.		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 RTECS: PM 4780000	dimethyl ether ♦ Flam. Gas 1A, H220 ♦ Acute Tox. 2, H330 Press. Gas (Comp.), H280	60-<70%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-0007	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 1	20-<25%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000 Reg.nr.: 01-2119484630-38-0000	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335 STOT SE 3, H336	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 01-2119488216-32-001 01-2119488216-32-002 01-2119488216-32-003	xylene Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Note: C	1-<5%
01-2119488216-32-003		

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

[•] After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed Coughing

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Page 4/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

· Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 8 for Information on personal protection eq

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

[·] Storage:

· Requirements to be met by storerooms and receptacles:

Observe label precautions. Store between 5 and 25 degrees Celcius in a dry, well ventilated place away from sources of heat, ignition and

direct sunlight. No smoking. Prevent access from unauthorised personell. Containers which are opened must be carefully resealed and kept

upright to prevent leakage. The storage and use of this product is subject to the requirements of the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). Up to 250 litres of such flammable liquids may be stored in a work area provided they are kept in a fire-proof cupboard or bin. Larger quantities must be kept in a separate storeroom conforming to the structural requirements of the regulations. Further guidance is contained in the HSE ACOP L135, "Storage of Dangerous Substances." UK.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from flammable substances.
- · Further information about storage conditions: Keep container tightly sealed.

Continue on page 5 GB Page 5/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

. 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

[•] 8.1 Control parameters

[•] Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm Sk

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

· Regulatory information WEL: EH40/2020

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Page 6/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. • For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of
- the following material are suitable: The breakthough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the baseis of the different substances in the preparation.
- · For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- · Eye protection:
- Safety glasses



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

[·] General Information

· Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
[·] pH-value:	Mixture is non-soluble (in water).
[.] Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-24.9 °C (115-10-6 dimethyl ether)
[·] Flash point:	< 0 °C
[·] Flammability (solid, gas):	Not applicable.
· Autoignition temperature:	235 °C
· Decomposition temperature:	Not determined.
[·] Ignition temperature:	Product is not selfigniting.
[·] Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	18.6 Vol %
[·] Vapour pressure at 20 °C:	5,200 hPa
[·] Density at 20 °C:	0.7075 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
[·] Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
	Continue on

Page 7/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

[•] Partition coefficient: n-octanol/water: Not determined.

· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	0 mm²/s
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	707.5 g/l
Solids content (volume):	0.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

[•] Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- * 10.3 Possibility of hazardous reactions No dangerous reactions known.
- * 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- [•] **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 12.069 mg/kg (rat) Dermal LD50 51.372 mg/kg (rabbit) Inhalative LC50/4 h 283 mg/l

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat) Dermal LD50 20,000 mg/kg (rabbit)

71-36-3 butan-1-ol

Oral LD50 790 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

Inhalative LC50/4 h 8,000 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

Continue on page 8 GB Page 8/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

- · Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- [•] **12.3 Bioaccumulative potential** No further relevant information available.
- * 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

12.5 Results of PBT and vPvB assessment

[•] PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).

- · vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

[·] Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Page 9/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

*

Trade name: SPRAY FILL

SECTION 14: Transport information	
14.1 UN-Number	
ADR, IMDG, IATA	UN1950
• 14.2 UN proper shipping name • ADR	
·IMDG	UN1950 AEROSOLS AEROSOLS
·IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
· Class	2 5F Gases.
·Label	2.1 Gases.
· IMDG, IATA	
· Class	2.1 Gases.
Label	2.1
14.4 Packing group	
· ADR, IMDG, IATA	Void
14.5 Environmental hazards:	N
Marine pollutant:	No
 <u>14.6 Special precautions for user</u> Hazard identification number (Kemler code): 	Warning: Gases.
· EMS Number:	- F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre:
	Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of
	living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
^{14.7} Transport in bulk according to Annex II	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not normitted as Excepted Quantity

Code: E0 Not permitted as Excepted Quantity Page 10/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

· Transport category	2
[·] Tunnel restriction code	D
·IMDG	
· Limited quantities (LQ)	1L
 Excepted quantities (EQ) 	Code: E0
	Not permitted as Excepted Quantity
[·] UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

- · Poisons Act
- · Regulated explosives precursors

SECTION 15: Regulatory information

- None of the ingredients is listed.
- · Regulated poisons
- None of the ingredients is listed.
- · Reportable explosives precursors
- 67-64-1 acetone: Listed
- · Reportable poisons
- None of the ingredients is listed.
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labelling: butan-1-ol
- acetone
- · Hazard statements
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- · Precautionary statements
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
- easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Trade name: SPRAY FILL

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- [·] Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and
- electronic equipment Annex II
- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed.
- Annex II REPORTABLE EXPLOSIVES PRECURSORS
- 67-64-1 acetone
- Regulation (EC) No 273/2004 on drug precursors
- 67-64-1 acetone: 3

• Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1

Bridging principles

Skin corrosion/irritation The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Specific target organ toxicity (single exposure)

· Department issuing SDS: Department of Quality Control

 Contact: HB BODY S.A
 Ms Olympia Stamkou
 Ph: +30 2310 790 032
 fax: +30 2310 790 033 Page 12/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

email: stamkou@hbbody.com ·* Data compared to the previous version altered.

GB Continue on page 13

Page 13/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

Annex: Exposure scenario 1

Short title of the exposure scenario

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU21 Consumer uses: Private households / general public / consumers

Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- [•] Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- Conditions of use According to directions for use.
- [•] Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- [·] Physical state Aerosol
- Concentration of the substance in the mixture The substance is main component.
- [·] Used amount per time or activity Smaller than 100 g per application.
- Other operational conditions
- [•] Other operational conditions affecting environmental exposure No special measures required.
- [•] Other operational conditions affecting worker exposure
- Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Other operational conditions affecting consumer exposure

No special measures required.

Keep out of the reach of children.

· Other operational conditions affecting consumer exposure during the use of the product Not applicable.

[•] Risk management measures

- [·] Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Avoid contact with the eyes.

Tightly sealed goggles

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Pregnant women should strictly avoid inhalation or skin contact.

[•] Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Page 14/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

Keep locked up and out of the reach of children.

- [·] Environmental protection measures
- · Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.
- · Soil The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.

[·] Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

[·] Waste type Partially emptied and uncleaned packaging

• Exposure estimation

[.] Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technitians only.

The highest inhalative exposure to be expected for consumers is 50 ppm.

The highest dermal exposure to be expected for consumers is 0.5 mg / kg / day.

The highest oral exposure to be expected for consumers is 0.5 mg / kg / day.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB Continue on page 15 Page 15/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

Annex: Exposure scenario 2

- Description of the activities / processes covered in the Exposure Scenario
- See section 1 of the annex to the Safety Data Sheet.
- Conditions of use According to directions for use.
- [.] Duration and frequency Frequency of use:

[•] Physical parameters

- The data on the physical chemical properties in the Exposure Scenario is based on the properties of the preparation.
- [·] Physical state Aerosol
- [•] Concentration of the substance in the mixture Raw material.
- Other operational conditions
- [•] Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- [•] Other operational conditions affecting consumer exposure No special measures required.
- [•] Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

- [·] Worker protection
- Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

[·] Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

The usual precautionary measures are to be adhered to when handling chemicals.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use selfcontained respiratory protective device.

• Measures for consumer protection Ensure adequate labelling.

Ensure adequate labelling.

- Observe consumer information and advice on safe use. • Environmental protection measures
- · Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- · Soil The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- [·] Disposal procedures
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging

[•] Exposure estimation

[.] Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technitians only.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB Continue on page 16 Page 16/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

Annex: Exposure scenario 3

- Description of the activities / processes covered in the Exposure Scenario
- See section 1 of the annex to the Safety Data Sheet.
- Conditions of use According to directions for use.
- [.] Duration and frequency Frequency of use:

[•] Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- [·] Physical state Fluid
- Concentration of the substance in the mixture Raw material.
- Other operational conditions
- [•] Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure Avoid contact with eves.
- Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

[•] Risk management measures

- [.] Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

- Technical protective measures
 Provide explosion-proof electrical equipment.
 Ensure that suitable extractors are available on processing machines
- · Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Measures for consumer protection
- Ensure adequate labelling.

Observe consumer information and advice on safe use.

- [·] Environmental protection measures
- · Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- · Soil The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- [.] Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

[·] Waste type Partially emptied and uncleaned packaging

• Exposure estimation

[.] Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technitians only.

Page 17/17 Printing date: 21.03.2024 Revision date: 21.03.2024 Version no. 27

Trade name: SPRAY FILL

[•] Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB