November, 2019





## **Peelable Glass Coating**

# Maintain crystal-clear lighting in your booth

Use Like90 Clear View glass coating to protect booth lights and windows. The water-based Clear View is applied with the same conventional equipment used to apply Like90 White Out and levels to a smooth transparent film that won't distort the booth's lighting or the clarity of its windows. As glass surfaces become clouded with overspray, simply peel and reapply Clear View.

### **Product Details**

Part numbers: 10034 - 1-gallon
Coverage: ~ 400 sq. ft/gallon
Color: White liquid, dries clear

• VOC: < 60g/L

• Shipping info: Not regulated for transport

## **Personal Protection**

- **Eye/face protection:** Avoid eye contact with vapors, mists, or spray. Safety glasses with side shields will provide additional protection.
- **Skin protection:** Select and use gloves and/or protective clothing to prevent skin contact after making an exposure assessment. Gloves made from neoprene or nitrile rubber are recommended.
- **Respiratory protection:** Avoid breathing of vapors, mists or spray. Use a particulate respirator in accordance with applicable safety regulations.

# **Application Instructions**

Spray equipment: Conventional, HVLP, Gravity Feed: air – 25 to 30 psi at gun; fluid tip 2.2 to 2.5mm.

NOTE: Use on glass only. Coating is not designed for other booth surfaces. Always apply Like90 Clear View after Like90 White Out has been applied.

- 1. Clean glass surfaces before first application. Remove any masking material used during White Out application.
- 2. Fill spray gun and adjust pressure to recommended equipment settings.
- 3. Apply 1 medium wet coat (3 to 4 mils) to lights and windows.
- 4. Allow surfaces to dry completely. Do not bake the coating dry.
- 5. Clean spray gun immediately with warm water.

#### Removal

- Remove and reapply Clear View on windows and lights if overspray becomes heavy. Clear View peels best at ambient temperatures (70° to 80° F).
- Clear View should be removed and reapplied at least every 6 months or 500 bake cycles. Peeled dry film is a solid waste. Dispose of in accordance with local regulations.

IMPORTANT NOTICE TO PURCHASER: The information in this document is based on tests that we believe are reliable. Your results may vary due to differences in test types and conditions. You must evaluate and determine whether the product is suitable for your intended application. Since conditions of product use are outside of our control and vary widely, the following is made in lieu of all express and implied warranties (including the implied warranties of merchantability and fitness for a particular purpose): Except where prohibited by law, Seller's only obligation and your only remedy, is replacement or, at Seller's option, refund of the original purchase price of product that is shown to have been defective when you received it. In no case will Seller be liable for any direct, indirect, special, incidental, or consequential damages (including, without limitation, lost profits, goodwill, and business opportunity) based on breach of warranty, condition or contract, negligence, strict tort, or any other legal or equitable theory.