

Rubberized Undercoat

4373

Rubberized Undercoat is designed for use on new panel and fender replacements, section repairs, weld joints and rust holes as a sound deadener and rust preventative. Seals out dust fumes, heat and cold. For best results use at room temperature.



Mix Ratio

Ready to use.



Suitable Substrates

- Painted or primed steel
- Bare steel

- Aluminum wheel wells
- Frame rails Galvanized steel
 - Bare aluminum



Surface Prep & Application

Clean with SCAT 6311, Speedi SCAT 6321 or Aqua SCAT 2 1391/1394. Shake well. Clean surface using SCAT 6311, Speedi SCAT 6321 or Agua SCAT 2 1391/1394. Holding can 8-10 inches from surface, apply 2-3 light even coats. Short, even strokes will produce best results. Remove overspray with Acry Solvent 9783/9784. When finished, invert can and spray until valve is free of material to prevent clogging. IMPORTANT: On cars equipped with catalytic converters, exhaust components operate at temperatures exceeding 1000°F (520°C). Therefore, avoid application of undercoating and/ or rust proofing materials within 12" of the exhaust system.



Product Specifications

Color	Black
Shelf life	3 years

Regulatory

Category	Undercoat
VOC content	<40% by weight



Limitations & Precautions

- This product provides adhesion & corrosion protection when used over noted (checked) substrates when properly cleaned, sanded & applied.
- Visit www.tat-co.com to assure use of the most current instructions and TDS on this product.
- See website (www.tat-co.com) for this document in other languages. (Vea el web site para este documento en español. Voir le site web pour ce document en français.)
- For use only by professional, trained painters. Not for sale to or use by the general public.
- · Before use, read and follow all TDS, label and SDS precautions.
- If mixed with other components, mixture may be hazards of all combined components.
- All Standard Operating Procedures (SOP) can be found on the Transtar website at www.tat-co.com.

LIMITED WARRANTY

The successful performance of this product is dependent on many factors beyond our control. Results are dependent upon the skill of the operator. This product is manufactured to meet the highest level of consistency and quality for the intended use. Transtar Autobody Technologies, Inc. warrants that its products meet the specifications which it sets for them. Should this product be proven to be off-specification within shelf life as stated in this datasheet, Transtar Autobody Technologies, Inc. will, at its sole discretion, either replace the product or issue credit for the original purchase price of the product. The replacement or refund shall be the buyer's sole remedy and Transtar Autobody Technologies, Inc. and its affiliates MAKE NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, DESIGN COMPATIBILITY AND FITNESS FOR A PARTICULAR PURPOSE. LABOR OR COST OF LABOR AND OTHER INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. The technical data contained herein are true and accurate to the best of our knowledge. Published technical data and instructions are subject to change without prior notice.